

# PRODUCT Data Sheet

## DeoxIT® Fader F5 Spray, F-Series Moving Contact Lubricant for Conductive Plastic Faders & Controls

### 1. Part No.:

F5S-H6

### 2. Container Size:

142 g (5.0 oz.), adjustable valve (L-M-H)

### 3. Product Description:

Precision lubricant for conductive plastics and carbon-based controls (faders, slide potentiometers, conductive membranes - mouse pads and other mechanisms with sliding surfaces). It replenishes lubrication lost on surfaces that have been cleaned with solvents or other cleaning solutions. Use on conductive plastics and other sliding metal-plastic surfaces. Temperature range: -26°C to +150°C.

### 4. Features/Benefits:

*Spray, adjustable valve (L-M-H) - Flushing action, Safe on plastics.*

DeoxIT® Fader F100L concentrate has approximately 0.0% chemical cleaning action.

DeoxIT® Fader is not for metal contacts/connectors, use DeoxIT®, DeoxIT® Gold and DeoxIT® Shield for those surfaces.

Replaces lubrication lost that have been cleaned with solvents or other cleaning solutions.

Perfect for OEM's

Excellent enhancing, excellent protection, No ozone depletion.

Reduces intermittent connections, arcing, RFI, wear and abrasion.

**Cleaner Audio - Clearer Video - Reliable Data.**

### 5. Formulation:

|     |   |
|-----|---|
| 5%  | DeoxIT® Fader F100L, F-Series             |
| 75% | Odorless mineral spirits (CAS 64742-88-7) |
| 20% | DIFLUOROETHANE (CAS 75-37-6)              |



### 6. Which DeoxIT® product do I Use:

- ▶ Use **DeoxIT® Fader F-Series** to lubricate and protect conductive plastic and carbon-based controls.
- ▶ Use **DeoxIT® D-Series** contact cleaner on surfaces that have been in service or have visual signs of oxidation. Contains 20% active cleaner.
- ▶ Use **DeoxIT® Gold G-Series** conditioner on new surfaces, and gold plated surfaces. Ideal for preventing dendrite/fretting corrosion. Protects both surface and base metals. Ideal for critical applications. Contains >1% active cleaner.
- ▶ Use **DeoxIT® Shield S-Series** to protect surfaces from severe environments (humidity, salts, pollutants, sulfur, etc.). Use on clean surface. Contains 0% active cleaner.



Home of the DeoxIT® family of  
Environmentally-Safer Contact Cleaners and  
Connector Enhancing Treatments  
Made in USA



Audio/Video



Computers



Automotive



Communications



Marine



Electrical



Energy



Photography



Security



Medical



Avionics

## 7. Directions for Use:

1. Turn off, unplug the device.
2. DeoxIT® Fader F-Series is for conductive plastic materials; however, there may be metal materials involved with the contact or control. On these metal surfaces that have been in service or have visual signs of oxidation or corrosion pre-treat with DeoxIT® D-Series (D5S-6) contact cleaner. See Data Sheet DS-D5S-6 and Audio/Video 9-1-1 Information Sheet (<http://store.caig.com/s.nl/it.l/id.52/f>).
3. Next, adjust valve (L-M-H) on the DeoxIT7 Fader F5S-H6 and utilizing the extension straw, apply one short burst of DeoxIT® Fader onto the plastic surface.
4. Operate the part/device to help distribute the DeoxIT® in the control or contact area. Wait a few seconds, reapply one short burst. **Test for compatibility before use.**
5. Wait two minutes before turning on equipment.
6. **For extended protection:** For additional lubrication and/or more tactile feel, apply DeoxIT® FaderGrease onto plastic surfaces; <http://store.caig.com/s.nl/sc.2/category.305/f>
7. **NOTE:** To prevent overspray or spraying in unwanted areas, you can always spray onto a lint-free swab or cloth first and then using the swab/cloth apply the DeoxIT® to the control/connector/contact surface(s).

## 8. Other Applicators:

| Part No.                 | % DeoxIT® | VOC (%) | Applicator       | Size    | Flammable/Nonflammable |
|--------------------------|-----------|---------|------------------|---------|------------------------|
| F5S-H6                   | 5%        | 75%     | spray            | 163 g   | flammable              |
| FN5MS-15                 | 5%        | 75%     | mini-spray       | 14 g    | nonflammable           |
| F100S-2                  | 100%      | 0%      | spray            | 57g     | nonflammable           |
| F100L-2C                 | 100%      | 0%      | tube             | 2 mL    | nonflammable           |
| F100L-25C                | 100%      | 0%      | needle dispenser | 25 mL   | nonflammable           |
| F5L-A (bulk, many sizes) | 5%        | 75%     | bottle/drum      | assort. | flammable              |

## 9. Product Selection Guides:

### DeoxIT® - Product Selection Guide

|                                   | DeoxIT®   | DeoxIT® GOLD | DeoxIT® GOLD GxL | DeoxIT® GOLD Gx2 | DeoxIT® SHIELD | DeoxIT® FaderLube |
|-----------------------------------|-----------|--------------|------------------|------------------|----------------|-------------------|
| New Surfaces                      |           | ✓            | ✓                | ✓                | ✓              | ✓                 |
| * In Service / Used               | ✓         |              |                  |                  |                | ✓                 |
| Gold surfaces                     |           | ✓            | ✓                | ✓                |                |                   |
| Oxidation / corrosion visible     | ✓         |              |                  |                  |                |                   |
| Conductive plastics               |           |              |                  |                  |                | ✓                 |
| ** Outdoor / Severe environments  | ✓         |              |                  |                  |                | ✓                 |
| Deoxidizing / cleaning properties | 20%       | 0.1%         | 0.1%             | 0.0%             | 0.0%           | 0.0%              |
| Metal / Plastic surfaces          | Yes       | Yes          | Yes              | Yes              | Yes            |                   |
| Plastics compatibility            | Excellent | Excellent    | Excellent        | Excellent        | Excellent      | Excellent         |
| Temperature range (°C)            | -34/200   | -45/240      | -45/310          | -45/500          | -34/210        | -26/150           |
| Stationary & moving surfaces      | Yes       | Yes          | Yes              | Yes              | Yes            | Yes               |
| Seals & protects base metals      | Good      | Excellent    | Excellent        | Excellent        | Good           | No                |

✓ All products are Nonflammable and RoHS Compliant

\* In Service: Clean with DeoxIT®. For added protection, follow with DeoxIT® GOLD (indoors), DeoxIT® SHIELD (outdoors) or DeoxIT® Grease (additional barrier).

\*\* Severe environments: Pre-clean with DeoxIT®. Follow with DeoxIT® SHIELD or DeoxIT® Grease.

### DeoxIT® - Spray Selection Guide

| Product Series   | FP | QD | NF | PC | VOC |
|--|----|----|----|----|-----|
| Standard - 5% solution   | ✓  |    |    | ✓  | 75  |
| D5S-6, D5MS-15, G5S-6, G5MS-15, S5S-6, S5MS-15, F5S-6, F5MS-15 |    |    |    |    |     |
| N Series - 5% solution   |    | ✓  | ✓  | ✓  | 20  |
| DN5S-6N, DN5MS-15, GN5S-6N, GN5MS-15, SN5S-6, SN5MS-15         |    |    |    |    |     |
| X Series - 5% solution   |    | ✓  | ✓  | ✓  | 20  |
| GX5S-6N  |    |    |    |    |     |
| 100 Series - 100% solution                                     |    |    | ✓  | ✓  | 0   |
| D100S-2, G100S-2, F100S-2                                      |    |    |    |    |     |

FP = Flushing properties QD = Quick dry / non drip NF = Nonflammable  
PC = Plastics compatibility VOC = VOC (%)



Audio/Video



Computers



Automotive



Communications



Marine



Electrical



Energy



Photography



Security



Medical



Avionics

## 10. Materials Compatibility (Plastics, Rubber, Elastomeric and Metals):

(Rating: Not compatible, Poor, Fair, Good, Excellent), (N/A = Not applicable (no solvents and propellants))

(\* If the product is not 100% DeoxIT® then the package is rated before and after the solvents/propellants are applied to materials. Compatibility testing is always recommended)

| Material Name      | Rating (*100% DeoxIT®) | Rating (*with solvents) |
|--------------------|------------------------|-------------------------|
| ABS                | Excellent              | Fair-Good               |
| Nylon              | Excellent              | Excellent               |
| Lexan              | Excellent              | Excellent               |
| HDPE               | Excellent              | Good                    |
| LDPE               | Good                   | Good                    |
| C.E.Phenolic       | Excellent              | Good                    |
| Epoxy              | Excellent              | Excellent               |
| Polycarbonate      | Excellent              | Fair-Good               |
| PMMA               | Good                   | Fair                    |
| POM                | Excellent              | Excellent               |
| PP                 | Excellent              | Good                    |
| PS                 | Good                   | Fair                    |
| PTFE               | Excellent              | Excellent               |
| PVC                | Excellent              | Excellent               |
| TPE/Rubber/Varnish | Fair                   | Poor                    |

### IMPORTANT:

**Rating, 100% DeoxIT®:** Any of the above that fall into the "Fair" and "Poor" categories should be thoroughly tested for compatibility. They may be compatible, however, it will depend on the manufacturing process of the materials. Acrylics, ABS, and polycarbonate, if under stress, may show slight cracking or crazing damage. Test for compatibility before use. On porous materials; i.e. wood, rubber, cloth, some phenolics, semi-cured materials, no liquid or solvents should be used. Occasionally, DeoxIT® will get onto unwanted surfaces, quickly wipe off surface and usually no damage will occur.

**Rating, with solvents:** Similar to rating above (100% DeoxIT®). However, any rating worse than the 100% DeoxIT® may require additional care. If DeoxIT is applied to unwanted areas or materials, wipe off surface quickly and usually no damage will occur. Alternatively, apply DeoxIT® onto a lint-free swab or cloth first and then wipe onto desired metal surface.

## 11. DeoxIT® Essential Reference:

**DeoxIT® D-Series** - Brings old systems back to life!


**DeoxIT® Gold G-Series** - Maintains new system performance!

**DeoxIT® Shield S-Series** - Maintains new system performance for severe environments!

**DeoxIT® Fader F-Series** - Clean, lubricate & protect conductive plastic and carbon compound faders!

## 12. Shipping and Additional Information:

Hazardous: ORMD  
VOC (%): Part No. F5S-H6, 75% (588 g/L)





Audio/Video



Computers



Automotive



Communications



Marine



Electrical



Energy



Photography



Security



Medical



Avionics

### 13. Other Information:

RoHS Compliant:

YES

VOC Compliant:

YES

**MSDS Link, F5S-H6**<http://store.caig.com/s.nl/sc.18/category.3545/f>

DeoxIT® Product Sheet:

<http://store.caig.com/s.nl/sc.18/category.236/f>

CAIG Essential Guide Link:

<http://store.caig.com/s.nl/it.l/id.73/f>

WHY DeoxIT® is Different:

<http://store.caig.com/s.nl/it.l/id.22/f><http://store.caig.com/s.nl/it.l/id.64/f>

### 14. MANUFACTURER DISCLAIMER:

To the best of our knowledge, the information contained herein is accurate. However, neither CAIG Laboratories, Inc., or any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. All materials may present unknown hazards and should be used with caution. In particular, improper use of our products and their inappropriate combination with other products and substances may produce harmful results which cannot be anticipated. Final determination of the suitability of any material is the sole responsibility of the user. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that may exist. All service performed on internal parts and equipment should be provided by qualified technicians.

### 15. Contact Information:



**Website:** [www.caig.com](http://www.caig.com)  
[www.deoxit.com](http://www.deoxit.com)

**General email:** [info@caig.com](mailto:info@caig.com)

**Technical email:** [tech@caig.com](mailto:tech@caig.com)

#### North America (Headquarters):

**CAIG Laboratories, Inc.**

12200 Thatcher Court  
 Poway, CA 92064 USA

Tel: (858) 486-8388

Fax: (858) 486-8398

#### Distributors (Domestic & International):

<http://store.caig.com/s.nl/sc.15/f>**CAIG Laboratories, Inc.**

12200 Thatcher Court, Poway, CA 92064 U.S.A.

**P:** 858/486-8388 | **E:** [info@caig.com](mailto:info@caig.com)**WEB:** [www.caig.com](http://www.caig.com) | [www.deoxit.com](http://www.deoxit.com)**Made in USA**