

BMFL™ Spot

The BMFL™ - Bright Multi-Functional Luminaire - much anticipated new lighting fixture from Robe, brings a real game changer in the world of moving lights.

The BMFL Spot™ has a custom light source designed for Robe and produces a staggering powerful 250 000 lux at 5 metres - no other product currently on the market can equal this output! Despite its power and comprehensive feature set, it weighs just 36 Kgs... and has a compact body profile. The lamp produces light at a CRI of 92+, this combined with a refined optical system, 5-55 degree zoom, results in a crisp, high quality fat beam that is truly homogenised and without a hotspot. There are also two colour wheels which include filters that can be utilised to adjust colour temperature and improve the CRI of the white output in aging lamps. There are two rotating gobo wheels - each with six slot&lock gobo positions. There are also two Rotating Prisms. The Dual Graphic Wheels both focus within the same focal plane and the rotation and movement can be individually controlled and varied... to create ultra-cool, infinitely subtle special effects. The frost and dimming functions provide further effects.

Three grades of Frost are available and the dimmer is exceptionally smooth with no distortion, so the full beam width is visible right up to the point at which it disappears. The strobe effect is authentic with up to 10 flashes per second! Aimed at long-throw applications, the newly patented Robe EMS™ (Electronic Motion Stabiliser) technology, enables the BMFL™ to absorb vibrations from audio outputs, truss movement, sprung or suspended floors, etc. The BMFL™ is a very powerful, feature packed luminaire that will provide a real signature light source for any project.



1700 W OSRAM Lok-it! HTI 1700/PS



40.000 lm, 250.000 lx @ 5 m, 2.500 lx @ 50 m



5° - 55°



2x gobo wheel, dual graphic wheel, circular and linear prism

Technical Specification

SOURCE

- Lamp: Compact short-arc metal halide lamp
- Base: PGJX28
- Approved model: OSRAM Lok-it! HTI 1700/PS
- Lifetime: 750 hours @ 1700 W / 1500 W / Quiet mode
- CRI 92+, Colour Temperature 6.000 K
- Control: Automatic and remote on/off
- Ballast: Electronic

OPTICAL SYSTEM

1. Robe's proprietary optical design
 2. High - efficiency zoom optical system, ratio 11:1
 3. Zoom range 5°-55°
 4. Output Lens diameter: 160 mm
 5. Dichroic glass reflector for maximising the light efficiency
 6. Fixture total lumen output:
 - 40.000 lm at 1700 W
 - 36.500 lm at 1500 W
 - 32.000 lm at 1200 W (Quiet mode)
- Light output: 250.000 lux @ 5m, 2.500 lux @ 50m

DYNAMIC EFFECTS

- Cyan: 0 - 100 %
- Magenta: 0 - 100 %
- Yellow: 0 - 100 %
- Variable CTO: 2.700 - 6.000 K
- Colour wheel 1 with 6 fixed dichroic colours: deep red, deep blue, orange, green, magenta, congo blue + white
- Colour wheel 2 with 6 replaceable "SLOT&LOCK" dichroic colours: pink, lavender, laser green, 9000 K CTB, minus half and minus green + white
- Rotating Gobo wheel 1:6 rotating, indexable, replaceable "SLOT&LOCK" glass gobos + open
- Rotating Gobo wheel 2:6 rotating, indexable, replaceable "SLOT&LOCK" glass gobos + open
- Dual Graphic Wheel with two animation discs, individual control of rotation of each disc
- Prism 1: 6 facet linear
- Prism 2: 6 facet circular
- Iris: Motorized, stepless, pulse effects up to 3 Hz
- Frost: variable Light, Medium and Heavy Frosts
- Motorized zoom and focus
- Shutter: Separate dual blade system, Variable strobe effect up to 10 Hz, full black out
- Dimmer: Optimized dual blade system for exceptional smooth dimming

CONTROL AND PROGRAMMING

- Setting & Addressing: ROBE Navigation System 2 (RNS2)
- Display: QVGA Robe touch screen with battery backup, gravitation sensor for auto screen positioning, operation

memory service log with RTC, stand-alone operation with 3 editable programs (each up to 100 steps), built-in analyser for easy fault finding

- Protocols: USITT DMX-512, RDM, ArtNet, MA Net, MA Net2, sACN
- Web server
- Wireless CRMX™ technology from Lumen Radio (on request)
- DMX Protocol modes: 2
- Control channels: 41, 33
- Pan/Tilt resolution: 16 bit
- CMY & CTO: 8 bit
- Colour wheel positioning: 8 or 16 bit
- Rotating Gobo Wheel positioning: 8 or 16 bit
- Gobo indexing & rotation: 8 or 16 bit
- Dual Graphic Wheel: 8 bit
- Iris: 8 or 16 bit
- Frost: 8 bit
- Zoom: 8 or 16 bit
- Focus: 8 or 16 bit
- Dimmer: 8 or 16 bit

ROTATING GOBOS

- 12x Rotating Glass gobos on 2 wheels
- Outside diameter: 30.8 mm
- Image diameter: 25.0 mm
- Thickness: 1.1 mm
- Max. thickness: 3.5 mm
- High temperature borofloat or better glass

THERMAL SPECIFICATION

- Maximum ambient temperature: 45 °C (113 °F)
- Maximum surface temperature: 100 °C (212 °F)
- Minimum operating temperature: -5°C (23°F)

ELECTRICAL SPECIFICATION

1. Power supply: Electronic auto-ranging
2. Input voltage range: 200-240 V, 50/60 Hz
3. Power consumption: 2000 W at 230 V / 50 Hz

Power in connector: Neutrik powerCON

DMX and RDM data in/out: Locking 3-pin & 5-pin XLR

Ethernet port in: RJ45

MECHANICAL SPECIFICATION

- Height: 813 mm (32") - head in vertical position
- Width: 483 mm (19")
- Depth: 335 mm (13.2")
- Weight: 36 kg (79.4 lbs)

RIGGING

- Mounting positions: 0°, 32° and 90°
- Universal operating position
- Mounting points: 5 pairs of 1/4-turn locking points
- 2x Omega adaptors with 1/4-turn quick locks
- Safety cable attachment point
- Pan and Tilt transport locks

ACCESSORIES

- Lamp Osram Lok-it HTI 1700/PS: 14080049
- BMFL Handles 2 pcs: 10980233
- BMFL Side Handle: 10980396
- Doughty Trigger Clamp: 17030386
- Safety wire 50 kg: 99011957
- Single Top Loader Case: 10120163-02
- Dual Top Loader Case: 10120164-02
- Foam Shell: 20020218-01

MOVEMENT

- Pan movement: 540°
- Tilt movement: 270°
- Movement control: Standard and Speed
- Controllable speed of Pan/Tilt movement
- EMS™: Electronic Motion Stabilizer system for Pan & Tilt reducing beam deviation caused by truss movement or vibration (Patent pending)
- Automatic Pan/Tilt position correction

EFFECT WHEEL

- Dual Graphic Wheel
- Material: Aluminium
- Diameter: 96 mm
- Can be used alone or in combination with rotating gobos
- Rotating in both directions, variable speed

APPROVALS

- CE Compliant
- cETLus Compliant

INCLUDED ITEMS

- User Manual
- Omega Adaptor CL-regular 2 pcs

- Power cord including powerCON In connector

LEGAL

- BMFL™ is a trademark of Robe lighting s.r.o.
- BMFL™ Spot is patented by Robe lighting s. r. o. and is protected by one or more pending or issued patent

gobos & colours

ROTATING GOBO WHEEL 1



15020290



15020291



15020292



15020293



15020294



15020295

ROTATING GOBO WHEEL 2




15020296



15020298



15020299



15020300



15020297



15020301

COLOUR WHEEL 1



14070411



14070393



14070394



14070395



14070396



14070397

COLOUR WHEEL 2



99014263



99014264



99014265



99014266



99014267



99014268