

theFAN™

The best complement to any atmospheric effect

Designed to work in tandem with our professional generators or as a stand alone unit, theFAN™ is a versatile, 100W, ultra-compact, variable speed, digital fan.



FEATURES

- Variable speed and air flow up to 850 CFM
- Free standing or variable mounting options
- Universal switching power supply 100 - 250 VAC, 50/60 Hz, single phase
- Noise Level at 1 m (3.3'): 64db at maximum speed
- 4 buttons LCD user interface, USITT DMX512, XLR-5 connectors, RDM compliant
- One-channel standard mode or two-channel quiet mode

TECHNICAL DATA

Mechanical	<ul style="list-style-type: none">• 3-bladed fan• 270° tilt• Variable speed• Airflow: 850 CFM• Noise Level: 64db at full speed• Omega clamp socket• M12 metric bolt hole	<ul style="list-style-type: none">• 0.5" imperial bolt hole• 2 handles• 4-button controller with LCD panel• Total net weight: 6.8kg (15 lb)• Total net size: 38 cm (15") H x 34.5 cm (13.95") W x 25.4 cm (10") D• Fan diameter: 26.4 cm (10.4")
Electrical	<ul style="list-style-type: none">• 100 - 250 VAC, 50/60 Hz, single phase• 100 Watts	
Data	<ul style="list-style-type: none">• 1 standard USITT DMX512 channel• 2 XLR-5 connectors: 1 input, 1 output• Controllable through DMX + RDM	
Digital Functions	<ul style="list-style-type: none">• Stand alone set speed• DMX Value	
Accessories	Flight case	
Approval	CE certified, CSA and UL approved	