

MEASUREMENT MICROPHONE
EMM-13D082/S-P48/RM

P48

> 125dBspl
3% distortion limit

Phantom power
Standard SPL capability 3% THD > 125dBspl
Noise < 28dB(A)









04.02.2010

Characteristics		Typ / Type	Nr./No.
miniXLR pin assignment Pin 1: Shield / Gnd Pin 2: signal + (hot) Pin 3: Signal - (cold)		EMM-13D082/S-P48/RM	140010
Nominal Microphone Diameter	mm	7 (1/4")	
Mikrophone characteristic	incidence 0°	Freefield / Freifeld	
polarization voltage	V	0	
Guaranteed frequency resp., uncal	± 1dB	100 - 5.000	± 1dB
calibrated frequency response		10 - 20.000	
Typ. class IEC (20Hz - 20kHz)	60541 class	1	
Sensitivity (mV) @ 1kHz	mV/Pa	30	
Sensitivity (dB re 1V) @ 1kHz	dB re 1V/Pa	-30	
3dB distortion limit	dBspl	> 125	
Phase matching (50Hz to 5kHz)	°	± 5	
Inherent noise (A-weighted)	dBspl	< 28	
Electrical			
Powering		Phantom	
excitation voltage	V	12..24...48	
Output Impedance	O	100 typ.	
Environmental			
Storage Temperature Range	deg C	-25 ... 70	
Operating Temperature Range	deg C	-10 ... 55	
Humidity (non condensing)	% r.H.	93	
Physical			
housing material		Stainless Steel / Edelstahl	
Dimensions (max. diameter x length)	mm x mm	12,7 x 82	
Acoustic Port Diameter	mm	7	
Weight	g	30	
Sealing		Polyurethane	
Output Connector		mini XLR	
Conformity			
		IEC 500081-1, IEC 61010-1	
Functionality /Accessories			
		>48V surge voltage protected optional 19mm bushing optional miniXLR - XLR cable	

iSEMcon GmbH. * Alexanderstr. 66 * 68519 Viernheim / Germany * Tel +49-6204-911 24 91 * Fax +49-6204-911 24 90 * sales@.iSEMcon.com
Subject to change without notice. Errors excepted.